



## Material Safety Data Sheet

### HP Marine Synthetic 2-Stroke Oil

**Date** : 03/15/2013  
**Version** : 4.X

## Section 1. Product and company identification

---

**Product name**

HP Marine Synthetic 2-Stroke Oil

**Material uses**

Lubricating oil. Not to be misted.

**Supplier/Manufacturer**

AMSOIL INC.  
925 Tower Avenue  
Superior, WI 54880

**Code**

HPM

**MSDS authored by**

AMSOIL INC.

**In case of emergency**

CHEMTREC, U.S. : 1-800-424-9300  
International: +1-703-527-3887

## Section 2. Hazards identification

---

Emergency overview

- Color** : Blue.
- Physical state** : Liquid. [Clear.]
- Odor** : Mild / Hydrocarbon.
- Signal word** : WARNING!
- Hazard statements** : COMBUSTIBLE LIQUID AND VAPOR. CAUSES EYE AND SKIN IRRITATION.
- Precautions** : Keep away from heat, sparks and flame. Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Wash thoroughly after handling.
- OSHA/HCS status** : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
- Routes of entry** : Dermal contact. Eye contact. Inhalation. Ingestion.

Potential acute health effects

- Inhalation** : No known significant effects or critical hazards.
- Ingestion** : No known significant effects or critical hazards.
- Skin** : Irritating to skin.
- Eyes** : Irritating to eyes.

Potential chronic health effects

- Chronic effects** : No known significant effects or critical hazards.
- Carcinogenicity** : No known significant effects or critical hazards.
- Mutagenicity** : No known significant effects or critical hazards.
- Teratogenicity** : No known significant effects or critical hazards.
- Developmental effects** : No known significant effects or critical hazards.
- Fertility effects** : No known significant effects or critical hazards.

Over-exposure signs/symptoms

- Inhalation** : No specific data.

- Ingestion** : No specific data.
- Skin** : Adverse symptoms may include the following:  
irritation  
redness
- Eyes** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness
- Medical conditions aggravated by overexposure** : None known.
- See toxicological information (Section 11)

## Section 3. Composition/information on ingredients

### United States

Name	CAS number	%
Solvent Mixture	64742-88-7	10 - 30

### Canada

Name	CAS number	%
Solvent Mixture	64742-88-7	10 - 30

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

## Section 4. First aid measures

- Eye contact** : Immediately flush eyes with plenty of water for at least 20 minutes, occasionally lifting the upper and lower eyelids. Get medical attention if symptoms occur.
- Skin contact** : After contact with skin, wash immediately with plenty of soap and water. Get medical attention if symptoms occur.
- Inhalation** : Move exposed person to fresh air. Get medical attention if symptoms occur.
- Ingestion** : Wash out mouth with water. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention if symptoms occur.
- Notes to physician** : No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

---

## Section 5. Fire-fighting measures

---

**Flammability of the product** : Combustible liquid.

**Extinguishing media**

**Suitable** : Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.

**Not suitable** : Do not use water jet or water-based fire extinguishers.

**Special exposure hazards** : Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

**Hazardous decomposition products** : No specific data.

**Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

---

## Section 6. Accidental release measures

---

**Personal precautions** : Shut off all ignition sources. No flares, smoking or flames in hazard area. Put on appropriate personal protective equipment (see Section 8).

**Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

**Methods for cleaning up**

**Small spill** : Absorb with an inert dry material and place in an appropriate waste disposal container. Use spark-proof tools and explosion-proof equipment. Dispose via a licensed waste disposal contractor.

**Large spill** : Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Use spark-proof tools and explosion-proof equipment. Dispose via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

---

## Section 7. Handling and storage

---

**Handling** : Put on appropriate personal protective equipment (see Section 8). Avoid contact with used product. Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use non-sparking tools. Take precautionary measures against electrostatic

discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Keep away from heat, sparks and flame. Do not reuse container.

**Storage**

- : Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

## Section 8. Exposure controls/personal protection

United States

Ingredient	Exposure limits
Solvent Mixture	<b>ACGIH TLV (United States, 1/2012). Absorbed through skin.</b> TWA: 200 mg/m <sup>3</sup> 8 hours. <b>OSHA PEL (United States, 6/2010).</b> TWA: 100 ppm 8 hours. TWA: 400 mg/m <sup>3</sup> 8 hours.

**Under conditions which may generate mists, the following additional exposure limits are recommended:**  
**ACGIH TLV TWA: 5 mg/m<sup>3</sup> ; STEL: 10 mg/m<sup>3</sup>.**

Canada

Occupational exposure limits		TWA (8 hours)			STEL (15 mins)			Ceiling			
Ingredient	List name	ppm	mg/m <sup>3</sup>	Other	ppm	mg/m <sup>3</sup>	Other	ppm	mg/m <sup>3</sup>	Other	Notations
Solvent Mixture	US ACGIH 1/2012	-	200	-	-	-	-	-	-	-	[1]

[1]Absorbed through skin.

**Under conditions which may generate mists, the following additional exposure limits are recommended:**  
**ACGIH TLV TWA: 5 mg/m<sup>3</sup> ; STEL: 10 mg/m<sup>3</sup>.**

Consult local authorities for acceptable exposure limits.

- Recommended monitoring procedures** : Personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment.
- Engineering measures** : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. Use explosion-proof ventilation equipment.
- Hygiene measures** : Ensure that eyewash stations and safety showers are close to the workstation location. Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

- Respiratory** : Not required under normal conditions of use. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Ensure a MSHA/NIOSH-approved respirator or equivalent is used.
- Hands** : Use gloves appropriate for work or task being performed. Recommended: Natural rubber (latex).
- Eyes** : Safety eyewear should be used when there is a likelihood of exposure. Recommended: Safety glasses with side shields.
- Skin** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. No special protective clothing is required. Recommended: Coveralls.

## Section 9. Physical and chemical properties

<b>Physical state</b>	: Liquid. [Clear.]	<b>Odor</b>	: Mild / Hydrocarbon.
<b>Color</b>	: Blue.	<b>pH</b>	: Not available.
<b>Flash point</b>	: Open cup: 86°C (186.8°F) [Cleveland.]	<b>Auto-ignition temperature</b>	: Not available.
<b>Flammable limits</b>	: Not available.	<b>Melting point/ Pour point</b>	: -46°C (-50.8°F)
<b>Boiling point</b>	: Not available.	<b>Vapor pressure</b>	: Not available.
<b>Relative density</b>	: 0.8697	<b>Vapor density</b>	: Not available.
<b>Volatility</b>	: Not available.	<b>Evaporation rate</b>	: Not available.
<b>Viscosity</b>	: Kinematic: 0.085 cm <sup>2</sup> /s (8.5 cSt) (100°C) Kinematic: 0.468 cm <sup>2</sup> /s (46.8 cSt) (40°C)	<b>Solubility</b>	: Not available.

## Section 10. Stability and reactivity

<b>Chemical stability</b>	: The product is stable.
<b>Conditions to avoid</b>	: Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.
<b>Materials to avoid</b>	: Reactive or incompatible with the following materials: oxidizing materials.
<b>Hazardous decomposition products</b>	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.
<b>Possibility of hazardous reactions</b>	: Under normal conditions of storage and use, hazardous reactions will not occur.
<b>Hazardous polymerization</b>	: Under normal conditions of storage and use, hazardous polymerization will not occur.

## Section 11. Toxicological information

### Acute toxicity

There is no data available.

### Chronic toxicity

There is no data available.

### Irritation/Corrosion

**Skin** : There is no data available.

**Eyes** : There is no data available.

**Respiratory** : There is no data available.

### Sensitizer

**Skin** : There is no data available.

**Respiratory** : There is no data available.

### Carcinogenicity

#### Classification

Product/ingredient name	ACGIH	IARC	EPA	NIOSH	NTP	OSHA
Solvent Mixture	A3	-	-	-	-	-

### Mutagenicity

There is no data available.

### Teratogenicity

There is no data available.

### Reproductive toxicity

There is no data available.

## Section 12. Ecological information

**Ecotoxicity** : No known significant effects or critical hazards.

### Aquatic ecotoxicity

Product/ingredient name	Result	Species	Exposure
Solvent Mixture	Acute LC50 2200 ug/L Fresh water	Fish - Lepomis macrochirus - 35 to 75 mm	4 days

### Persistence/degradability

There is no data available.

## Section 13. Disposal considerations

**Waste disposal** : The generation of waste should be avoided or minimized wherever possible. This material and its container must be disposed of in a safe way. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Empty containers or liners may retain some product residues. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

## Section 14. Transport information

**DOT/TDG/IMDG/IATA** : Not regulated.

## Section 15. Regulatory information

### United States

**HCS Classification** : Combustible liquid  
Irritating material

**U.S. Federal regulations** : **United States inventory (TSCA 8b)**: All components are listed or exempted.  
**SARA 302/304**: No products were found.  
**SARA 311/312 Hazards identification**: Fire hazard, Immediate (acute) health hazard

**Clean Air Act Section 112 (b) Hazardous Air Pollutants (HAPs)** : Not listed

**Clean Air Act Section 602 Class I Substances** : Not listed

**Clean Air Act Section 602 Class II Substances** : Not listed

**DEA List I Chemicals (Precursor Chemicals)** : Not listed

**DEA List II Chemicals (Essential Chemicals)** : Not listed

### State regulations

**Massachusetts** : None of the components are listed.

**New York** : None of the components are listed.

**New Jersey** : The following components are listed: Distillates (petroleum), hydrotreated heavy paraffinic

**Pennsylvania** : None of the components are listed.

**California Prop. 65**

No products were found.

**Canada**

**WHMIS (Canada)** : Class B-3: Combustible liquid with a flash point between 37.8°C (100°F) and 93.3°C (200°F).  
Class D-2B: Material causing other toxic effects (Toxic).

**Canadian lists**

**Canadian NPRI** : The following components are listed: Solvent Mixture

**CEPA Toxic substances** : None of the components are listed.

**Canada inventory** : All components are listed or exempted.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

## Section 16. Other information

**United States**

**Label requirements** : COMBUSTIBLE LIQUID AND VAPOR. CAUSES EYE AND SKIN IRRITATION.


**Hazardous Material Information System (U.S.A.)** :

Health	1
Flammability	1
Physical hazards	0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

**National Fire Protection Association (U.S.A.)** :



**Date of issue** : 03/15/2013

**Date of previous issue** : 04/26/2012

**Version** : 4.X

**Notice to reader**

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.